

CHEMICAL RESISTANCE CHART



PRODUCTS

		ACIDS																															
		Acetic Acid 10%	Benzoic Acid-Sat @3%	Boric Acid-Sat @30%	Butyric Acid 10%	Chromic Acid 10%	Citric Acid 50%	Diglycolic Acid	Fatty Acids	Fluoboric Acid	Formic Acid 10%	Hydrochloric Acid 15%	Hydrochloric Acid 37%	Hydrofluoric Acid	Hydrogen Peroxide to 20%	Hydrochlorous Acid 5%	Lactic Acid to 20%	Maleic Acid 30%	Maleic Acid 50%	Methanol Chloride	Methylene Chloride	Nitric Acid 10%	Nitric Acid 30%	Oleic Acid; Oxalic Acid-Sat	Perchloric Acid 35%	Phosphoric Acid 35%	Picric Acid-Sat	Succinic Acid-Sat	Sulfuric Acid 25%	Sulfuric Acid 50%	Sulfuric Acid 98%	Tannic Acid; Tartaric Acid-Sat	
Flooring	Krete-Seal 800	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Krete-Seal Fast 820	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Strong-Krete Fast 830	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Strong-Krete Fast 850	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Chemical Mortar 840	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	Krete-Chemical 870	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	Krete-Fex 880	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Industrial Floor 600	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
Rebuilding Epoxy	Rebuild 101	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Rebuild Underwater 121	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Rebuild Fast 151	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Rebuild Chemical 201	*	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	Rebuild Chemical Fast 251	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	High Temp Putty 1800	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	Abrasion 306HT	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	Abrasion 301	*	1	1	4	1	1	1	3	4	*	*	*	*	2	1	1	1	*	*	*	*	*	1	4	1	1	1	1	1	1	*	1
	Abrasion 303	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Abrasion 306	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Abrasion Fast 351	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
	Abrasion Fast 353	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1	
Abrasion Fast 356	*	1	3	4	1	1	1	3	4	*	*	*	*	2	3	3	1	*	*	*	*	*	1	4	3	1	3	3	3	*	1		
Epoxy Coating	Metal 400	*	1	2	2	1	1	1	2	4	1	2	*	1	1	2	2	1	1	*	*	1	2	1	2	2	1	2	2	2	*	1	
	Metal-Flex 480	*	1	2	2	1	1	1	2	4	1	2	*	1	1	2	2	1	1	*	*	1	2	1	2	2	1	2	2	2	*	1	
	Industrial 620	*	1	2	2	1	1	1	2	4	1	2	*	1	1	2	2	1	1	*	*	1	2	1	2	2	1	2	2	2	*	1	
	Low Surface Energy 290	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	Chemical 200	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	
	Chemical 200HT	4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	2	2	1	1	1	1	1	1	1	1	1	1	1	

1 = Excellent; Suitable for Immersion 2 = Very Good; Suitable for Immersion
 3 = Good; Suitable for Secondary Containment 4 = Fair; Spill / Splash * = Not Recommended

CHEMICAL RESISTANCE CHART



PRODUCTS

	CAUSTICS																	SOLVENTS													
	Aluminum Chloride 50%	Ammonia 20%+	Ammonium Chloride 50%	Ammonium Hydroxide 40%	Ammonium Nitrate-Sat	Ammonium Persulfate	Ammonium Sulfate-Sat	Calcium Chloride 50%	Calcium Hydroxide-Sat	Calcium Hypochlorite 15%	Copper Fluoroborate	Ferric Chloride; Ferrous Sulfate	Sodium Benzoate	Sodium Carbonate (Soda Ash)	Sodium Bicarbonate-Sat	Sodium Bisulfate; Sodium Chloride-Sat	Sodium Glutamate	Sodium Hydroxide to 50%	Sodium Hypochlorite to 10%	Sodium Propionate	Sodium Sulfate; Sulfite-Sat	Trisodium Phosphate-Sat	Zinc Nitrate	Methanol	Ethanol	Butanol; Propanol	Benzene; Xylene; Toluene	Trichloroethane; Cellosolve	Formaldehyde to 37%	Gasoline; Fuel Oil; Crude Oil	Acetone; MEK; Methylene Chloride
Flooring	Krete-Seal 800	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	3	3	3	3	3	3	*
	Krete-Seal Fast 820	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	3	3	3	3	3	3	*
	Strong-Krete Fast 830	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	3	3	3	3	3	3	*
	Strong-Krete Fast 850	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	3	3	3	3	3	3	*
	Chemical Mortar 840	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	4	1	1	1	1	1	1	4
	Krete-Chemical 870	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	4	1	1	1	1	1	1	4
	Krete-Fex 880	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	3	3	3	3	3	3	*
	Industrial Floor 600	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	3	3	3	3	3	3	*
Rebuilding Epoxy	Rebuild 101	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	4	2	1	1	1	1	1	4	
	Rebuild Underwater 121	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	2	1	1	1	1	1	*	
	Rebuild Fast 151	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	4	2	1	1	1	1	1	4	
	Rebuild Chemical 201	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	3	1	1	1	1	1	1	3
	Rebuild Chemical Fast 251	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	3	1	1	1	1	1	1	3
	High Temp Putty 1800	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	3	1	1	1	1	1	1	3
	Abrasion 306HT	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	3	1	1	1	1	1	1	3
	Abrasion 301	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	2	1	1	1	1	1	*
	Abrasion 303	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	2	1	1	1	1	1	*
	Abrasion 306	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	2	1	1	1	1	1	*
	Abrasion Fast 351	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	2	1	1	1	1	1	*
	Abrasion Fast 353	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	2	1	1	1	1	1	*
Abrasion Fast 356	1	1	1	1	1	1	1	1	3	1	3	1	1	1	1	1	1	3	1	1	1	3	*	2	1	1	1	1	1	*	
Epoxy Coating	Metal 400	1	1	1	1	1	1	1	1	1	2	1	1	1	1	1	1	2	1	1	1	2	*	2	1	1	1	1	1	*	
	Metal-Flex 480	1	1	1	1	1	1	1	1	1	2	1	1	1	1	1	1	2	1	1	1	2	*	2	1	1	1	1	1	*	
	Industrial 620	1	1	1	1	1	1	1	1	1	2	1	1	1	1	1	1	2	1	1	1	2	*	2	1	1	1	1	1	*	
	Low Surface Energy 290	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	3	1	1	1	1	1	1	3
	Chemical 200	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	3	1	1	1	1	1	1	3
Chemical 200HT	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	3	1	1	1	1	1	1	3	

1 = Excellent; Suitable for Immersion 2 = Very Good; Suitable for Immersion
 3 = Good; Suitable for Secondary Containment 4 = Fair; Spill / Splash * = Not Recommended