

PRODUCT APPLICATION GUIDE

PRODUCTS		Metal	Concrete	<70°C(158°F) Immersion	<150°C(300°F) Immersion	<230°C(446°F) Immersion	Concentrated Acid	Diluted Acid	Alkaline	Food and Drugs compliance (FDA)	Mild Erosion	Moderate Abrasion	Severe Abrasion	Extreme Abrasion	Mild to Moderate Impact	Moderate to Severe Impact
Flooring	Krete-Seal 800		X	X				X	X		X					
	Krete-Seal Fast 820		X	X				X	X		X					
	Strong-Krete 830		X	X				X	X				X		X	
	Strong-Krete Fast 850		X	X				X	X				X		X	
	Chemical Mortar 840		X	X			X		X				X		X	
	Krete-Chemical 870		X	X			X		X	X			X			
	Krete-Flex 880		X	X				X	X		X					
	Industrial Floor 600		X	X				X	X		X					
Rebuilding Epoxy	Rebuild 101	X			X			X	X	X		X				
	Rebuild Underwater 121	X		X				X	X			X				
	Rebuild Fast 151	X			X			X	X	X		X				
	Rebuild Chemical 201	X				X	X		X	X		X				
	Rebuild Chemical Fast 251	X				X	X		X	X		X				
	High Temp Putty 1800	X				X	X		X	X		X				
	Abrasion 306HT	X				X	X		X					X		X
	Abrasion 301	X		X				X	X				X			X
	Abrasion 303	X		X				X	X				X			X
	Abrasion 306	X		X				X	X					X		X
	Abrasion Fast 351	X		X				X	X				X			X
	Abrasion Fast 353	X		X				X	X				X			X
	Abrasion Fast 356	X		X				X	X					X		X
	Epoxy Coating	Metal 400	X			X			X	X	X		X			
Metal-Flex 480		X		X				X	X			X				
Industrial 620		X		X				X	X			X				
Low Surface Energy 290		X	X			X	X		X	X		X				
Chemical 200		X		X			X		X	X		X				
Chemical 200HT		X				X	X		X	X		X				